



U.S. Sized Non-Ferrous Blades

• **NEGATIVE RAKE ANGLE**




Negative Rake / TCG
These non-ferrous circular saw blades are used for miter cross-cut saws and saw benches without fixed work piece clamping and with manual or automatic feeding.

• **POSITIVE RAKE ANGLE**



Positive Rake / TCG
Use pomiter cross-cut saws and saw benches non-ferrous circular saw blades for table saw machines. This design prevents the material from lifting during manual feeding.

• **TRIPLE CHIP GRIND**



Dia.	Teeth	Bore	Kerf	Plate	Heavy Duty Metal Miter	Standard Metal Miter	Screen Extr. Metal Miter
9"	60	5/8"	.105	.085		MM096003	
9"	80	5/8"	.100	.085	MM098003H		
9"	80	5/8"	.105	.085		MM098003	
10"	80	5/8"	.110	.095	MM108003H		
10"	80	5/8"	.115	.095		MM108003	
10"	96	5/8"	.095	.075			MMS10962AF
10"	100	5/8"	.110	.095		MM101003	
10"	100	5/8"	.115	.095	MM101003H		
11"	90	5/8"	.115	.095		MM119003	
12"	90	5/8"	.110	.095	MM129003H		
12"	90	5/8"	.115	.095		MM129003	
12"	100	5/8"	.115	.095		MM121003	
12"	100	5/8"	.110	.095	MM121003H		
12"	120	5/8"	.110	.095	MM121203H		
12"	120	5/8"	.115	.095		MM121203	
12"	120	5/8"	.105	.085			MMS121202AF
13"	80	1"	.120	.100		MM138003	
13"	100	1"	.120	.100		MM131003	
14"	100	1"	.125	.105		MM141003	
14"	120	1"	.125	.105		MM141203	
16"	100	1"	.125	.105		MM161003	
16"	120	1"	.125	.105		MM161203	
16"	130	1"	.125	.105		MM161303	
16"	150	1"	.125	.105		MM161503	
20"	150	1"	.165	.120		MM201503	
20"	180	1"	.165	.120		MM201803	
22"	180	1"	.165	.120		MM221803	

WHEN ORDERING:

If a negative rake is required, add an (N) at the end of the catalog number.

If a positive rake is required, add a (P) at the end of the catalog number.

NOTE: Larger saw blade diameters are available upon request.

For safety purposes, General Saw Corporation recommends using optimum cooling and lubrication when cutting non-ferrous metals.